



Shandong Zhaoyue Bearing Co., Ltd.



20 mm x 52 mm x 15 mm KOYO NUP304R
cylindrical roller bearings

Bearing No. NUP304R

NUP304R Bearing 2D drawings and 3D CAD models

Size	20x52x15 mm
Bore Diameter	20 mm
Outer Diameter	52 mm
Width	15 mm
d	20 mm
Fw	27.5 mm
D	52 mm
B	15 mm
C	15 mm
r min.	1.1 mm
r1 min.	0.6 mm
Weight	0.153 Kg
Basic dynamic load rating (C)	31.5 kN
Basic static load rating (C0)	26.9 kN
(Grease) Lubrication Speed	12000 r/min
Bearing No.	NUP304R
r(min)	1.1
r1(min)	0.6
Cr	39.4
C0r	26.9
Cu	3.75
Grease lub.	12000
Oil lub.	16000
Ew	-
d1	-



Shandong Zhaoyue Bearing Co., Ltd.

B1	-
B2	-
da(min)	26.5
db(min)	24
db(max)	27
dc(min)	-
dd(min)	-
Da(max)	45.5
Db(max)	-
Db(min)	-
ra(max)	1
rb(max)	0.6
(Refer.)Mass(kg)	0.163